

Ladders



300Lbs Fibreglass Extra Heavy Duty Type 1A Step Ladders 486 Series



Molded Top With Handyman's Tool Slots
Rugged, nonconductive structural molded top is extremely durable. Molded-in slots help keep tools close at hand.



Full Channel Fiberglass Rail
Nonconductive full channel front and back rails are covered with a polyester veil for years of service without fiber prominence or blooming.



Reinforced Bottom Back Brace
Heavy Duty bottom back brace provides additional strength to the bottom of the ladder.



Inside Spreader Braces
Spreader braces inside fiberglass rails help protect braces from getting hooked or abused in transit.



Double-Rivet Step Construction
Each step secured with six, large headed, semi-tubular steel rivets for maximum strength. 30% greater shear strength than solid aluminum rivets.



Slip Resistant Feet
Aluminum angel feet with thick tread on all four legs to provide better footing. Tread can be replaced when necessary.

SKU	Model	Size (ft)	Approx. Spread	Base Width
1680048606	486 - 06	6	40"	22 7/8"
1680048608	486 - 08	8	52"	25 7/8"
1680048610	486 - 10	10	65"	28 7/8"
1680048612	486 - 12	12	78"	31 7/8"



300Lbs Fibreglass Heavy Duty Industrial Rated Type 1A Twin Front Ladder 530 Series



Heavy Gauge Steel Hinges
Heavy duty hinge assembly design exceeds industry standards for maximum durability.



Inside Spreader Braces
Steel spreader braces located inside of side rails help protect braces from damage in transit.



Slip Resistant Feet
Aluminum angel feet with thick tread on all four legs to provide better footing. Tread can be replaced when necessary.



Double-Rivet Step Construction
Each step secured with six, large headed, semi-tubular steel rivets for maximum strength. 30% greater shear strength than solid aluminum rivets.



Full Channel Fiberglass Rail
Nonconductive full channel front and back rails are covered with a polyester veil for years of service without fiber prominence or blooming.

SKU	Model	Size (ft)	Approx. Spread	Base Width
1680053010	530 - 10	10	83"	28 7/8"
1680053012	530 - 12	12	98"	31 7/8"

Material Handling

Ladders



375Lbs FM1400HD Series

Fiberglass Extra Heavy Duty Type IAA Twin Front Ladder



Heavy Gauge Steel Hinges
Heavy duty hinge assembly design for maximum durability.



Da Boot
Polypropylene computer upper boot provides strength, durability and fiberglass rail surface protection. Thick non-marring thermoplastic elastomer tread is bonded and mechanically fastened to the upper boot and provides a slip resistant footing. Inside, Da Boot has a unique open design that allows for quick and easy visual inspection of fiberglass rail.



Inside Spreader Braces
Spare braces inside fiberglass rails help keep braces from getting hooked or abused during transit.



Heavy Double Gusset Bracing
Heavy duty steel gussets on each step and angel back braces.



Riveted Step Construction with gussets
Each step features heavy duty steel gussets secured with large-headed, semi-tubular steel rivets for maximum strength. 30% greater shear strength than solid aluminum rivets.



Spreader Brace Reinforcement Plates
Four key stress areas are reinforced with steel plates to prolong ladder life.



Full Channel Fiberglass Rail
Nonconductive full channel rails are covered with a polyester veil for years of durable service.

SKU	Model	Size (ft)	Approx Spread	Base Width
1680001414	FM - 1414HD	14	113"	33 7/8"
1680001416	FM - 1416HD	16	128"	36 7/8"



225Lbs 592 Series

Fiberglass Commercial Duty Rated Step Ladders



Molded Top with Handyman's Tool Slots
Rugged, non-conductive structural molded top is extremely durable. Molded-in slots help keep tools close at hand.



Slip Resistant Feet
Aluminum angle feet with thick tread on both legs to provide better footing. Feet can be replaced when necessary.



Full Channel Fiberglass Front Rails
Non-conductive full channel rails are covered with a polyester veil for years of service with out fiber prominence or blooming.



Pinch Resistant Spreader Braces
Heavy duty plated steel spreader braces with double rivet hinge to protect user from pinched fingers.

SKU	Model	Size (ft)	Approx. Spread	Base Width
1680059204	592 - 04	4	28"	19 7/8"
1680059205	592 - 05	5	34"	21 3/8"
1680059206	592 - 06	6	40"	22 7/8"
1680059207	592 - 07	7	47"	24 3/8"
1680059208	592 - 08	8	52"	25 7/8"

Ladders



300Lbs 534 Series

Fiberglass Extra Heavy Duty Industrial Rated Extension Ladder



QuickLatch
QuickLatch equipped ringlock provides easier method of securing fly and base sections when extended. One-finger operation. Patent #5429207



D-Shaped Rungs
Flat top, D-shape provides greater standing area than round rungs. Fully serrated for slip-resistant surface.



Swivel Safety Shoes
Heavy duty plated steel shoes with thick rubber tread. Shoe can be used with tread down or spike position.



Mar-Resistant Rail End Caps
Impact resistant caps on all rail ends provide rail protection for longer life and protect work surfaces from marring.



Outside Slide Guides
Two extra heavy outside slide guides secured to top of base section with four rivets per guide for maximum strength. Over extending stop on fly section.

SKU	Model	Total Length (ft)	Max. Extended length (ft)
1680053420	534-20	20	17
1680053424	534-24	24	21
1680053428	534-28	28	25
1680053432	534-32	32	29



225Lbs 618 Series

Fiberglass Commercial Duty Rated Extension Ladders



Swivel Safety Shoes
Extra heavy duty cast aluminum shoes with thick tread. Exclusive design features full swivel safety shoe that can be used with tread down or in spike position.



QuickLatch
QuickLatch equipped ringlock provides easier method of securing fly and base sections when extended. One-finger operation. Patent #5429207



D-Shaped Rungs
Tempered aluminum rungs are hydraulically double crimped to side rails and serrated for a slip-resistant surface. D-shape provides greater standing area than round rungs.



Mar-Resistant Rail End Caps
Impact resistant, polycarbonate caps on all rail ends provide rail protection for longer life and help protect work surfaces from marring.

SKU	Model	Total Length (ft)	Max Ext. Length (ft)
1648061816	618 - 16	16	13
1648061820	618 - 20	20	17
1648061824	618 - 24	24	21

Material Handling

Ladders



225Lbs 405 Series

Aluminum Commercial Duty Rated Type II Extension Ladders



D-Shaped Rungs
Big 1-5/8" tempered aluminum rungs are hydraulically double crimped to side rails and serrated for a slip-resistant surface. Greater standing area than round rungs.



Mar-Resistant Rail End Caps
Impact resistant polycarbonate caps on all rail ends for protection, longer life and durability. The caps also help protect work surfaces from marring.



Slip Resistant Treads
Ladder features treads on free aligning, extruded aluminum shoes.



Rope and Pulley
Aluminum 1-1/4" pulley standard on all sizes except 16'. Comes with a 5/16" durable polypropylene rope for all weather performance.



QuickLatch
QuickLatch equipped ruglock provides easier method of security fly and base sections when extended. One-finger operation.

SKU	Model	Total Length (ft)	Max Ext. Length (ft)
1680040516	405 - 516	16	13
1680040520	405 - 520	20	17
1680040524	405 - 524	24	21
1680040528	405 - 528	28	25

PICA - Handrail Wide Step Ladder




SKU	Model	Dimension (mm)	Weight (kg)
1649501203	CTB3BA	H660 W510 D700	3.6
1649501204	CTB4BA	H890 W550 D855	4.2
1649501205	CTB5BA	H1120 W595 D1010	4.9

Characteristics:


- Broad step, easy operation
- Easy to fold. 110mm width after folded, super-thin
- Surface oxidized

Ladders

PICA - Dual-Utilities Step Ladder



self-supporting "A" type ladder
K-210D-A



a long straight ladder

AL

MAX
100kg

no-tool

75°


S

SKU	Model	Dimension (mm)	Weight (kg)
1649502005	K150DA	H391 W577 D1035	5.5
1649502006	K180DA	H1683 W630 D1214	6.7
1649502007	K210DA	H1974 W684 D1392	8.6

Characteristics:

- ↗ Dual-utilities as "A" type ladder or a long straight ladder
- ↗ Light, artistic, practical

PICA - Wide Step Ladder



AL

MAX
100kg

no-tool

widened

SKU	Model	Dimension (mm)	Weight (kg)
1649502308	JOB-240-A	H2270 W737 D1571	9.9
1649502309	JOB-270-A	H2560 W791 D1749	11.6
1649502310	JOB-300-A	H2850 W844 D1928	12.9


Characteristics:

- ↗ Light, artistic, practical
- ↗ Step width 55mm
- ↗ Strong and durable

Material Handling

Ladders

PICA - Working Platform DWD



DWD-K808-A

AL

MAX
100kg


folded

SKU	Model	Dimension (mm)	Weight (kg)
1649503002	DWD-K808-A	H850 W447 D1374	6.2

Characteristics:

- ⇨ Pothook lockable device
- ⇨ Rigidity enforced step
- ⇨ Foldaway, easy for storage
- ⇨ Different height for selecting

PICA - Working Platform With Extension Ceiling



DWV-S86-A

AL

MAX
100kg

folded

oxidized

SKU	Model	Dimension (mm)	Weight (kg)
1649503103	DWV-S86-A	H550~859 W387~443 D1372~2131	10.0

Characteristics:

- ⇨ Pothook lockable device
- ⇨ Each support can be adjusted according to different purposes
- ⇨ Foldaway, easy for storage
- ⇨ Different height for selecting
- ⇨ The top board can be extended according to requirement.
- ⇨ Height of top step 930-1500mm

Ladders

PICA - Adjustable Working Platform DWX



DWX-6908-A



SKU	Model	Dimension (mm)	Weight (kg)
1649503102	DWX-6908-A	H602~911 W414~471 D1229~1418	6.3

Characteristics:

- Pothook lockable device
- Each support can be adjusted according to different purposes
- Foldaway, easy for storage
- Different height for selecting



Material Handling

Ladders



150Kg Heavy Industrial Duty Aluminium Step Ladder

Special Features

- ✔ Safety Insured with high hardness aluminium.
- ✔ Non -Skid rubber footing prevent slipping
- ✔ Grooved for secured footing
- ✔ Maintenance free
- ✔ High Stability

Single Pole

Height
8'
10'
12'
15'

Double Extension

Height
14' (8' x 8')
18' (10' x 10')
22' (12' x 12')
28' (15' x 15')
34' (18' x 18')
38' (20' x 20')

Triple Extension

Height
20' (8' x 8' x 8')
26' (10' x 10' x 10')
32' (12' x 12' x 12')
41' (15' x 15' x 15')
50' (18' x 18' x 18')
56' (20' x 20' x 20')



150Kg Heavy Industrial Duty Aluminium Step Ladder

Special Features

- ✔ Safety Insured with high hardness Aluminium.
- ✔ Non -Skid rubber footing prevent slipping
- ✔ Grooved for secured footing
- ✔ Maintenance free
- ✔ High Stability

Steps	H	W	L
03	29"	18.5"	15"
04	38"	27"	16"
05	48.5"	31"	18.5"
06	58"	33"	20"
07	67"	43"	20"
08	77"	46"	22"
09	87"	51"	22.5"
10	97"	55"	24"
11	107"	58.5"	24.5"
12	117.5"	57.5"	27"
14	137"	60.5"	31"
15	146"	69"	32"
16	156"	80"	33.5"
18	175"	85"	36"
20	195"	95"	37.5"
22	213"	114"	41.5"