

Air Equipment

Screw Driver

MV-6216B



- Compact and easy to use
- Adjustable torque - clutch type
- Ideal for light assembly industries

MV-6226B



- Pistol Grip



MID-50

- Compact, light weight & powerful
- Double-Dog Hammer mechanism for power vs weight
- Ideal for all kind of assembly jobs



MID-60

MI-12D



- Twin Hammer Clutch
- Tease Throttle for precise control
- One handed easy reverse switch

Model	Driver Chuck Hex	Bolt Cap	Max Torque	Net Weight	Overall Length	Free Speed	Avg. Air Cons	Air Inlet	Hose Size
	(in)	(mm)	(kg.m)	(kg)	(mm)	(rpm)	(m ³ /min)	(pt)	(in)
MV-6216B	1/4	6	10.9	1.20	250	1,800	0.15	1/4	3/8
MV-6226B	1/4	6	11.2	1.30	205	1,800	0.15	1/4	3/8
MID-50	1/4	6	15.0	0.55	162	10,000	0.20	1/4	3/8
MID-60	1/4	8	19.8	0.90	207	10,000	0.35	1/4	3/8
MI-12D	1/4	12	21.0	1.20	150	10,000	0.40	1/4	3/8

Specifications: Air Pressure 6kg/cm²

Torque: 1.0kg.m = 9.807N.m = 7.233 ft.lb

CKD Filter



SKU

Description

021410402

CKD Filter F3000 - 8F



SKU

Description

021410403

CKD Filter F4000 - 10F